

| SN030 24VDC | |
|-----------------------------------|--------------------------------------|
| Technical parameters: | |
| Recommended oil tank capacity | up to 1 000 litres |
| El. Power supply | 26 VDC |
| El. Engine | 385 W |
| Flow rate | max. 2 litres / min. (46cSt at 40°C) |
| Working pressure, max. pressure | 5.0 bar, 6.5 bar |
| Hose supply inlet | 1/2" or quick couplings |
| Outlet hose supply | 1/2" or quick couplings |
| Vent valve | 1/4" |
| Drain valve | 1/4" |
| Number of filter bodies | 1 pcs T35 |
| Suction filter | 1 pcs / 250 µm |
| Max. and min. working temperature | -10°C to 60°C |
| Viscosity | 2 to 150 cSt |
| Degree of protection IP | IP 54 |
| Dimensions (l x w x h) | 460 x 270 x 440 mm |
| Weight | approx. 28 kg |

SN030 24VDC is a product of ECOFIL Slovakia and meets all STN, ISO and EU standards.



The manufacturer ECOFIL Slovakia reserves the right to change the design and colour of the equipment!

| SN060 24VDC | |
|-----------------------------------|---|
| Technical parameters: | |
| Recommended oil tank capacity | up to 2 000 litres |
| El. Power supply | 26 VDC |
| El. Engine | 385 W |
| Flow rate | max. 4 litres / min. (46cSt at 40°C) |
| Working pressure, max. pressure | 5.0 bar, 6.5 bar |
| Hose supply inlet | 1/2" or quick couplings |
| Outlet hose supply | 1/2" or quick couplings |
| Vent valve | 1/4" |
| Drain valve | 1/4" |
| Number of filter bodies | 2 pcs T35 |
| Suction filter | 1 pcs / 250 µm |
| Max. and min. working temperature | -10°C to 60°C |
| Viscosity | 2 to 150 cSt |
| Degree of protection IP | IP 54 |
| Dimensions (l x w x h) | 580 x 270 x 440 mm |
| Weight | approx. 36 kg |

SN060 24VDC is a product of ECOFIL Slovakia and meets all STN, ISO and EU standards.



The manufacturer ECOFIL Slovakia reserves the right to change the design and colour of the equipment!