

<b>SN060 – model 35 ATEX</b>	
Technical data:	
Recommended volume of oil tank	<b>max. 3000 lit.</b>
Connection to electricity ATEX	<b>230 V (50 Hz) ATEX</b>
El. Motor (consumption)	<b>0,370 kW</b>
Flow	<b>max. 6,0 lit/min at (46cSt/40°C)</b>
Max. pressure	<b>8 Bar</b>
Inlet with hoses connection	<b>quickcoupling or G 1/2"</b>
Outlet with hoses connection	<b>quickcoupling or G 1/2"</b>
Numbers of filtration unit T35	<b>2 pcs</b>
Suction filter	<b>1 pc / 125 µm</b>
Possible achieved oil cleanliness class	<b>NAS 4/5 ISO 16/14/11</b>
Max. working temperature	<b>80°C</b>
Viscosity	<b>from 6 to 400 cSt</b>
Dimensions (length x width x height)	<b>650 x 500 x 970</b>
Weight	<b>50 kg</b>

**SN060 model 35 ATEX is product of ECOFIL Slovakia company and the product meets all STN, ISO and standards valid in the EU.**



***The manufacturer ECOFIL Slovakia reserves the right to change the design and colour of the devices!***

SN120 model 35 ATEX	
Technical data:	
Recommended volume of oil tank	max. 5 000 lit.
Connection to electricity ATEX	3x230V/400V 50Hz or 230V/50 Hz
El. Motor (consumption)	0,750 kW
Flow	max. 12 lit. / min.
Max. pressure	8 Bar
Inlet with hoses connection	quickcoupling or 3/4" G
Outlet with hoses connection	quickcoupling or 3/4" G
Numbers of filtration unit T35	4 pcs
Suction filter	1 pc / 100 µm
Possible achieved oil cleanliness class	NAS 4/5 ISO 16/14/11
Max. working temperature	80°C
Viscosity	6 to 460 cSt
Dimensions (length x width x height)	800 x 500 x 970 mm
Weight	max. 100 kg

SN120 model 35 ATEX is product of ECOFIL Slovakia company and the product meets all STN, ISO and standards valid in the EU.



*The manufacturer ECOFIL Slovakia reserves the right to change the design and colour of the devices!*

SN180 model 35 ATEX	
Technical data:	
Recommended volume of oil tank	from 5 000 to 8 000 lit.
Connection to electricity ATEX	3x230V/400V 50Hz or 230V/50 Hz
El. Motor (consumption)	0,750 kW
Flow	max. 12 lit. / min.
Max. pressure	8 Bar
Inlet with hoses connection	quickcoupling or G 3/4"
Outlet with hoses connection	quickcoupling or G 3/4"
Numbers of filtration unit T35	6 pcs
Suction filter	1 pc / 100 µm
Possible achieved oil cleanliness class	NAS 4/5 ISO 16/14/11
Max. working temperature	80°C
Viscosity	6 to 460 cSt
Dimensions (length x width x height)	1160 x 500 x 970 mm
Weight	max. 120 kg

SN180 model 35 ATEX is product of ECOFIL Slovakia company and the product meets all STN, ISO and standards valid in the EU.



*The manufacturer ECOFIL Slovakia reserves the right to change the design and colour of the devices!*

SN240 model 35 ATEX	
Technical data:	
Recommended volume of oil tank	from 5 000 to 8 000 lit.
Connection to electricity ATEX	3x230V/400V 50Hz or 230V/50 Hz
El. Motor (consumption)	1,1 kW
Flow	max. 12 lit. / min.
Max. pressure	8 Bar
Inlet with hoses connection	quickcoupling or G 3/4"
Outlet with hoses connection	quickcoupling or G 3/4"
Numbers of filtration unit T35	8 pcs
Suction filter	1 pc / 100 µm
Possible achieved oil cleanliness class	NAS 4/5 ISO 16/14/11
Max. working temperature	80°C
Viscosity	6 to 460 cSt
Dimensions (length x width x height)	1400 x 500 x 970 mm
Weight	max. 140 kg

SN240 model 35 ATEX is product of ECOFIL Slovakia company and the product meets all STN, ISO and standards valid in the EU.



*The manufacturer ECOFIL Slovakia reserves the right to change the design and colour of the devices!*