

| SN030 – model EASY                                          |                                           |
|-------------------------------------------------------------|-------------------------------------------|
| Technical parameters:                                       |                                           |
| Oil tank capacity                                           | max. 1000 lit.                            |
| Electrical supply                                           | 230 V (50 Hz), 24V, adapter 230 V (50 Hz) |
| Electric motor                                              | 370 W by 230V                             |
| Flow rate (variable – adjustable)                           | 3,0 lit. / min. pri (46cSt/40°C)          |
| Maximum pressure                                            | 8 Bar                                     |
| Hose inlet and outlet connections                           | 9/16 UNF                                  |
| Number of filter housings                                   | 1 ks                                      |
| Suction filter                                              | 1 ks / 100 µm                             |
| Achievable oil cleanliness class                            | NAS 4/5 ISO 16/14/11                      |
| Maximum water content after filtration                      | <100 mg/lit                               |
| Quantity of filter elements T351, H351, HH351, WE351, WG351 | 1 ks                                      |
| Maximum operating temperature                               | 80°C                                      |
| Viscosity                                                   | od 6 do 680 cSt                           |
| Dimensions (length × width × height) mm                     | 340 x 240 x 750                           |
| Weight                                                      | max. 30 kg                                |

**Optional equipment:** NEURON® monitoring

**The SN030 EASY 230V model is a product of ECOFIL® Slovakia and meets all applicable STN, ISO, and EU standards.**



*photo: version with el. motor 230V*



*version with ECO motor BLDC + NEURON® monitoring of filtration*

*Manufacturer ECOFIL® Slovakia reserves the right to change the design and colour scheme of the equipment!*